

ACESSÓRIOS ELETRODUTOS





REDUÇÕES



com rosca BSP
56124/



sem rosca
56125/



REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [mm]		
				A	B	C
reduções com rosca						
56124/001	48	01087 9	¾" x ½"	22	14	
56124/002	36	01088 6	1" x ½"	22	12	
56124/003	36	01089 3	1" x ¾"	22	12	
56124/004	36	01090 9	1¼" x ½"	30	18	
56124/005	36	01091 6	1¼" x ¾"	30	18	
56124/006	36	01092 3	1¼" x 1"	30	18	
56124/008	24	01093 0	1½" x ¾"	31	18	
56124/009	24	01094 7	1½" x 1"	31	18	
56124/010	24	01095 4	1½" x 1¼"	31	18	
56124/013	24	01096 1	2" x 1"	34	20	
56124/015	24	01097 8	2" x 1½"	34	20	
56124/021	12	01098 5	2½" x 2"	40	26	
56124/028	6	01099 2	3" x 2½"	45	30	
56124/036	6	01100 5	4" x 3"	56	40	



CONECTORES RETOS



unidut cônico
sem rosca BSP
56126/0



box reto
com rosca BSP
56127/0



reduções sem rosca [acompanham parafusos]

56125/001	24	01101 2	¾" x ½"	22	26	50
56125/002	24	01102 9	1" x ½"	22	32,5	50
56125/003	24	01103 6	1" x ¾"	28	32,5	55

conector reto sem rosca [acompanham parafusos]

56126/001	50	01107 4	½"	22	15	45
56126/002	50	01108 1	¾"	28	16	48
56126/003	20	01109 8	1"	34,5	16	52
56126/007	5	00660 5	2½"	78	22	71
56126/008	5	00661 2	3"	90,5	24	80
56126/010	5	00662 9	4"	116,5	28	90

conector reto com rosca [acompanham parafusos e arruelas]

56127/001	100	00899 9	½"	22	15	45
56127/002	100	00900 2	¾"	28	16	48
56127/003	50	00901 9	1"	34,5	16	52
56127/007	5	00905 7	2½"	78	22	71
56127/008	5	00906 4	3"	90,5	24	80
56127/010	5	00907 1	4"	116,5	28	90



CONECTORES FLEXOR



unidut cônico
sem rosca BSP
56126/0



box reto
com rosca BSP
56127/0





conector flexor reto sem rosca [acompanham parafusos]

56126/021	50	04437 9	½"	22	10	35
56126/022	50	04438 6	¾"	28	10	35
56126/023	30	04439 3	1"	34,5	10	35
56126/024	20	05791 1	1¼"	43	11	44
56126/025	10	05792 8	1½"	49	11	44
56126/026	10	05793 5	2"	61	11	44

conector flexor reto com rosca [acompanham parafusos e arruelas]


56127/021	100	05140 7	½"	22	10	35
56127/022	100	05141 4	¾"	28	10	35
56127/023	50	05142 1	1"	34,5	10	35
56127/024	20	05785 0	1¼"	43	11	44
56127/025	20	05786 7	1½"	49	11	44
56127/026	10	05787 4	2"	61	11	44

CONECTORES CURVOS




REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [mm]		
				A	B	C
conector curvo com rosca [acompanham parafusos e arruelas]						
56128/001	50	00908 8	½"	22	26,5	15,5
56128/002	50	00909 5	¾"	27,5	26	15,5
56128/003	20	00910 1	1"	34,5	32	16
56128/004	20	02054 0	1¼"	43	35	19
56128/005	10	02055 7	1½"	51,5	40	20
56128/006	10	02056 4	2"	64,5	45	22
56128/007	5	02057 1	2½"	78	78	28
56128/008	5	02058 8	3"	91	91	30
56128/010	5	02059 5	4"	117	70	35
conector curvo sem rosca [acompanham parafusos]						
56129/001	50	00917 0	½"	22	26,5	
56129/002	50	00918 7	¾"	27,5	26	
56129/003	20	00919 4	1"	34,5	32	
56129/004	20	02060 1	1¼"	43	35	
56129/005	10	02061 8	1½"	51,5	40	
56129/006	10	02062 5	2"	64,5	45	
56129/007	5	02063 2	2½"	78	50	
56129/008	5	02064 9	3"	91	60	
56129/010	5	02065 6	4"	117	70	

LUVAS DE EMENDA



luvas de emenda [acompanham parafusos]						
56131/001	50	01104 3	½"	22	55	
56131/002	25	01105 0	¾"	28	60	
56131/003	20	01106 7	1"	34,5	66	
56131/007	5	00654 4	2 ½"	77	95	
56131/008	5	00655 1	3"	90	110	
56131/010	5	00656 8	4"	115,5	125	

LUVAS DE EMENDA FLEXOR




luvas de emenda flexor [acompanham parafusos]						
56131/021	50	04440 9	½"	22	45	
56131/022	50	04441 6	¾"	28	45	
56131/023	25	04442 3	1"	34,5	45	
56131/024	20	05788 1	1 ¼"	43	58	
56131/025	10	05789 8	1 ½"	49	58	
56131/026	10	05790 4	2"	61	58	

CONECTORES PRENSA-CABOS

Podem ser utilizados para vedação das entradas de cabos elétricos em caixas ou em outros aparelhos. Possuem uma bucha cônica de aperto e vedação para a acomodação do cabo elétrico.




alumínio
56132/0



poliamida
56132/2



poliamida
56132/3




Verde	Terra	Cinza	Preto
-------	-------	-------	-------

REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [mm]			BUCHA	COR
				A	B	C		
alumínio [possuem rosca padrão BSP tipo gás]								
56132/001	50	01110 4	3/8"	10,5	25	10	6 a 7,5	
56132/004	50	01113 5	½"	15,5	32	13	10 a 12,5	
56132/008	50	01117 3	¾"	20,5	38	15	15 a 17,5	
56132/010	50	01119 7	1"	25,5	45	18	20 a 22,5	
56132/055	50	02368 8	½"	15,5	32	13	3,0 a 5,5	
56132/059	50	02396 1	¾"	20,5	38	15	3 a 5,5	
56132/063	50	02400 5	1"	25,5	45	18	6 a 8,5	
56132/002	50	01111 1	3/8"	10,5	25	10	7,5 a 9	
56132/005	50	01114 2	½"	15,5	32	13	12,5 a 15	
56132/009	50	01118 0	¾"	20,5	38	15	17,5 a 20	
56132/011	50	01120 3	1"	25,5	45	18	22,5 a 25	
56132/054	50	02367 1	3/8"	10,5	25	10	5,5 a 8	
56132/056	50	02369 5	½"	15,5	32	13	5,5 a 8	
56132/060	50	02397 8	¾"	20,5	38	15	5,5 a 8	
56132/064	50	02401 2	1"	25,5	45	18	8,5 a 11	
56132/003	50	01112 8	3/8"	10,5	25	10	9 a 10	
56132/007	50	01116 6	¾"	20,5	38	15	12,5 a 15	
56132/066	50	02403 6	1"	25,5	45	18	13,5 a 16	
56132/006	50	01115 9	¾"	20,5	38	15	10 a 12,5	

REF.	EMB.	789.1435.	ROSCA	Ø	CABOS	DIMENSÃO [mm]			CHAVE	COR
BSPMin.Máx.ABCmm										
poliamida [possuem rosca padrão BSP tipo gás]										
56132/250	50	02766 2	¾"	3	6,5	20	8	13,15	15	
56132/251	50	02767 9	3/8"	5	10	24	8	16,55	22	
56132/252	50	02768 6	½"	6	12	27	9	20,95	24	
56132/253	50	02769 3	¾"	13	18	30	11	26,44	33	
56132/254	50	02770 9	1"	18	25	38	11	33,25	42	
56132/255	25	02832 4	1¼"	22	32	45	13	41,91	53	
56132/256	25	02833 1	1½"	32	38	47	14	47,8	65	
56132/257	25	02834 8	2"	37	44	47	15	59,6	65	
56132/350	50	02824 9	¾"	3	6,5	20	8	13,15	15	
56132/351	50	02825 6	3/8"	5	10	24	8	16,66	22	
56132/352	50	02826 3	½"	6	12	27	9	20,95	24	
56132/353	50	02827 0	¾"	12	18	30	11	26,44	33	
56132/354	50	02828 7	1"	18	25	38	11	33,25	42	
56132/355	25	02829 4	1¼"	22	32	45	13	41,91	53	
56132/356	25	02830 0	1½"	32	38	47	14	47,8	65	
56132/357	25	02831 7	2"	37	44	47	15	59,6	65	

BUCHAS


Fabricadas em **liga de alumínio**,
possuem rosca padrão BSP [tipo gás].



REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [mm]		
				A	B	C
buchas [alumínio]						
56134/001	200	01121 0	3/8"	22	7,5	13
56134/002	200	01122 7	½"	25,5	8,5	15,5
56134/003	200	01123 4	¾"	31	9	21
56134/004	200	01124 1	1"	38,5	10	27
56134/005	200	01125 8	1¼"	48	11	33
56134/006	200	01126 5	1½"	54,5	12,5	41
56134/007	100	01127 2	2"	66,5	13	53
56134/008	40	01128 9	2½"	83,5	15,5	67
56134/009	40	01129 6	3"	97	16,5	78
56134/011	20	01130 2	4"	122	18	103

ARRUELAS

Fabricadas em **liga de alumínio e zinco [zamak]**,
possuem rosca padrão BSP [tipo gás].



arruela [alumínio]						
56135/001	200	01140 1	3/8"	26	4	
56135/002	200	01141 8	½"	26	4	
56135/003	200	01142 5	¾"	32	4	
56135/004	200	01143 2	1"	40	5	
56135/005	200	01144 9	1 ¼"	49	5	
56135/006	200	01145 6	1 ½"	55	5	
56135/007	100	01146 3	2"	69	5,5	
56135/008	40	01147 0	2 ½"	83	6,5	
56135/009	40	01148 7	3"	96	8,5	
56135/011	20	01149 4	4"	124	9	

ABRAÇADEIRAS

Fabricadas em **aço carbono**, recebem acabamento **galvanizado eletrolítico**.

Tipo D



56136/0

56136/1

Tipo U



56137/0

56137/1

Tipo Chaveta



56138/0

56138/1

REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [mm]		
				A	B	C
tipo D [fornecidas com parafuso e porca]						
56136/002	200	01159 3	½"	20	19	49,5
56136/003	200	01160 9	¾"	25,2	19	53
56136/004	200	01161 6	1"	31,5	19	62
56136/005	100	01162 3	1 ¼"	40,5	27,5	71
56136/006	100	01163 0	1 ½"	46,6	27,5	75
56136/007	100	01164 7	2"	58,4	27,5	92
56136/008	50	01165 4	2 ½"	74,1	27,5	110,5
56136/009	50	01166 1	3"	86,8	27,5	130
56136/011	50	01167 8	4"	111,6	27,5	154
embalagens [3 unidades]						
56136/102	20	04040 1	½"	20	19	49,5
56136/103	20	04041 8	¾"	25,2	19	53
56136/104	20	04042 5	1"	31,5	19	62

tipo U

56137/002	200	01168 5	½"	20	19	51,5
56137/003	200	01169 2	¾"	25,2	19	60
56137/004	200	01170 8	1"	31,5	19	70
56137/005	100	01171 5	1 ¼"	40,5	27,5	84
56137/006	100	01172 2	1 ½"	46,6	27,5	94
56137/007	100	01173 9	2"	58,4	27,5	98
56137/008	50	01174 6	2 ½"	74,1	27,5	125
56137/009	50	01175 3	3"	86,8	27,5	140
56137/011	50	01176 0	4"	111,6	27,5	158
embalagens [3 unidades]						
56137/102	20	04043 2	½"	20	19	51,5
56137/103	20	04044 9	¾"	25,2	19	60
56137/104	20	04045 6	1"	31,5	19	70

tipo chaveta

56138/002	200	01177 7	½"	20	27,5	39
56138/003	200	01178 4	¾"	25,2	27,5	42
56138/004	200	01179 1	1"	31,5	27,5	55
56138/005	100	01180 7	1 ¼"	40,5	27,5	61
56138/006	100	01181 4	1 ½"	46,6	27,5	68
56138/007	100	01182 1	2"	58,4	27,5	80
56138/008	50	01183 8	2 ½"	74,1	27,5	96
56138/009	50	01184 5	3"	86,8	27,5	115
56138/011	50	01954 4	4"	111,6	27,5	136
embalagens [3 unidades]						
56138/102	20	04046 3	½"	20	27,5	39
56138/103	20	04047 0	¾"	25,2	27,5	42
56138/104	20	04048 7	1"	31,5	27,5	55

Indicado para todos os tipos de eletrodutos de aço-carbono conforme norma NBR 5624.